

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) A magnetic recording medium comprising:

a non-magnetic base material; [[and]]

a ferromagnetic metal layer of a cobalt based alloy formed on top of said non-magnetic base material; [[with]] and

a metal underlayer disposed between said base material and said ferromagnetic metal layer ~~therebetween~~, wherein,

a coercive force H_c is at least 2000 (Oe), [[and]]

an anisotropic magnetic field H_k^{grain} is at least 10,000 (Oe), and

said metal underlayer incorporates an underfilm of either one of Cr and a Cr alloy, and said Cr alloy also incorporates Mo and/or W.

2. (original) A magnetic recording medium according to claim 1, wherein said metal underlayer and said ferromagnetic metal layer are formed in a film fabrication chamber with an ultimate vacuum at a 10^{-9} Torr level, using a film fabrication gas with an impurity concentration of no more than 1 ppb.

[3. (canceled)]

4. (previously presented) A magnetic recording medium according to claim 1, wherein said metal underlayer incorporates an underfilm of either one of Cr and a Cr alloy, and said Cr alloy incorporates one, or two or more elements selected from a group consisting of V, Nb, Hf, Zr, Ti, Mn, Ta, Ru, Re, Os, Ir, Rh, Pd, Pt, P, B, Si, Ge, N and O.

C2
Contd
5. (previously presented) A magnetic recording medium according to any one of claim 1, wherein a film thickness of said metal underlayer is within a range from 3 nm to 20 nm.

6. (previously presented) A magnetic recording medium according to claim 1, wherein said metal underlayer comprises a layered structure of two or more underfilms with different lattice constants.

7. (original) A magnetic recording medium according to claim 6, wherein said metal underlayer is a two layered construction with a second underfilm layered on top of a first underfilm, and a film thickness ratio t_2/t_1 of a film thickness t_1

of said first underfilm and a film thickness t_2 of said second underfilm is within a range from 0.2 to 5.0.

8. (original) A magnetic recording medium according to claim 7, wherein a film thickness of said first underfilm is within a range from 1.5 nm to 8.5 nm.

9. (previously presented) A magnetic recording medium according to claim 7, wherein a film thickness of said second underfilm is within a range from 1.5 nm to 8.5 nm.

10. (previously presented) A magnetic recording medium according to claim 1, wherein a lattice misfit of said metal underlayer and said ferromagnetic metal layer, as determined by an equation $(y-x) / (x/2 + y/2) \cdot 100(\%)$, in which x represents a length obtained by multiplying by $\sqrt{2}$ a lattice constant of said metal underlayer and y represents a c axis length of a crystal lattice of said ferromagnetic metal layer, is a value from 0.5% to 2.5%.

11. (original) A magnetic recording medium according to claim 10, wherein said lattice misfit of said metal underlayer and said ferromagnetic metal layer is a value from 0.5% to 1.5%.

12. (previously presented) A magnetic recording medium according to claim 1, wherein in a crystal lattice of said ferromagnetic metal layer of said cobalt based alloy, an interatomic distance a in a direction of a normal line to said ferromagnetic metal layer is larger than an interatomic distance b in a direction within a plane of said ferromagnetic metal layer.

13. (original) A magnetic recording medium according to claim 12, wherein an axial length ratio a/b of said interatomic distance a in a direction of a normal line to said ferromagnetic metal layer relative to said interatomic distance b in a direction within a plane of said ferromagnetic metal layer is within a range from 1.002 to 1.008.

[14-16 (canceled).]

17. (previously presented) A magnetic recording device comprising a magnetic recording medium according to claim 1, a drive section for driving said magnetic recording medium, and a magnetic head for carrying out recording and playback of magnetic information, wherein said magnetic head performs recording and playback of magnetic information on a moving said magnetic recording medium.

18. (canceled)

19. (currently amended) A magnetic recording medium according to ~~any one of~~ claim 2, wherein said metal underlayer comprises a layered structure of two or more underfilms with different lattice constants.

20. (currently amended) A magnetic recording medium according to claim 3 1, wherein said metal underlayer comprises a layered structure of two or more underfilm with different lattice constants.

21. (new) A magnetic recording medium, comprising:
a non-magnetic base material;
a metal underlayer formed on top of said non-magnetic base material and incorporating an underfilm of either one of Cr and a Cr alloy incorporating Mo or W; and

a ferromagnetic metal layer of a cobalt based alloy formed on top of said non-magnetic base material and said ferromagnetic metal layer so that said metal underlayer disposed between said base material and said ferromagnetic metal layer, wherein,

at a same time, a coercive force H_c is at least 2000 (Oe), and an anisotropic magnetic field H_k^{grain} is at least 10,000 (Oe).

22. (new) The magnetic recording medium of claim 21, wherein, said underfilm comprises the Cr alloy incorporating Mo.

23. (new) The magnetic recording medium of claim 21, wherein, said underfilm comprises the Cr alloy incorporating W.

24. (new) The magnetic recording medium of claim 21, wherein, said underfilm comprises the Cr alloy incorporating Mo and W.
